

Material Safety Data Sheet

Issuing Date 23-Nov-2011

Revision Date

Revision Number 0

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name Carbon Steel / Alloy Steel

Recommended Use Cold Drawn Steel Bars

Distributor

ThyssenKrupp Materials NA, Inc.
22355 W. Eleven Mile Road
Southfield, Michigan 48034
TEL: 248-233-5681

Emergency Telephone Number 248-233-5681

2. HAZARDS IDENTIFICATION

WARNING!

Emergency Overview

Non-combustible as supplied.
Small chips, fines and dust from processing may be readily ignitable.
Hazardous fumes can also occur in post-processing operations
Product dust may be irritating to eyes, skin and respiratory system.
Dust may form explosive mixture in air
Possibly cancer hazard by inhalation

Appearance Metallic, Solid

Physical State Solid.

Odor Odorless

OSHA Regulatory Status

General Hazard Statement: Solid metallic products are generally classified as "articles" and do not constitute hazardous materials in solid form under the definitions of the OSHA Hazard Communication Standard (29 CFR 1910.1200). Any articles manufactured from these solid products would be generally classified as non-hazardous. However, some hazardous elements contained in these products can be emitted under certain processing conditions such as but not limited to: burning, melting, cutting, sawing, brazing, grinding, machining, milling, and welding.

Potential Health Effects

Principle Routes of Exposure

Eye contact. Skin contact. Inhalation.

Acute Toxicity

Eyes
Skin

Dust contact with the eyes can lead to mechanical irritation.
Contact with dust can cause mechanical irritation or drying of the skin. Contact with oils from processing may cause irritation. Prolonged skin contact may defat the skin and produce dermatitis. Repeated or prolonged skin contact may cause allergic reactions with susceptible persons.

Inhalation

May be harmful if inhaled. Inhalation of dust in high concentration may cause irritation of respiratory system. Inhalation of fumes may cause metal-fume fever.

Ingestion

May be harmful if swallowed. May cause additional affects as listed under "Inhalation".

Chronic Effects

Repeated contact may cause allergic reactions in very susceptible persons. Avoid repeated exposure. Prolonged exposure may cause chronic effects. Repeated or prolonged skin contact may cause skin irritation and/or dermatitis and sensitization of susceptible persons. May cause central nervous system depression with nausea, headache, dizziness, vomiting, and incoordination. May cause adverse effects on the bone marrow and blood-forming system. May cause adverse liver effects.

Elevated temperature processing such as welding and plasma arc cutting may release hazardous fumes. Overexposure to metal fumes may cause pulmonary edema (fluid in the lungs) and methemoglobinemia. May also cause pulmonary fibrosis and lung cancer. Lead compounds may be absorbed by ingestion, by inhalation and through the skin. Lead may damage kidney function, the blood forming system and the reproductive system. Inorganic lead compounds can cause developmental damage.

Aggravated Medical Conditions

Allergies. Skin disorders. Respiratory disorders. Central nervous system. Pre-existing eye disorders. Blood disorders. Kidney disorders. Liver disorders. Nasal cavities. Lungs.

Interactions with Other Chemicals

Irritants. Sensitizers. Epoxies. Use of alcoholic beverages may enhance toxic effects.

Environmental Hazard

Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. See Section 12 for additional Ecological Information.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Each alloy may contain one or more of the following ingredients. Consult the Technical Data Sheet for the composition of specific alloys.

Chemical Name	CAS-No	Weight %
Iron	7439-89-6	97.00 - 99.00
Nickel	7440-02-0	0.01-3.75
Chromium	7440-47-3	0.01-2.50
Manganese	7439-96-5	0.25-1.65
Molybdenum	7439-98-7	0.01-1.10
Carbon	7440-40-0	0.01-1.10
Copper	7440-50-8	0.01-0.50
Silicon	7440-21-3	0.01-0.5
Tellurium	13494-80-9	0.01-0.50
Lead	7439-92-1	0.15-0.35
Sulfur dioxide	7446-09-5	0.001-0.35
Vanadium pentoxide	1314-62-1	0.01-0.25
Bismuth	7440-69-9	0.01-0.10
Aluminum	7429-90-5	0.01- 0.1
Phosphorus	7723-14-0	0.01-0.04

Iron alloys may be comprised of all or variations of the alloys shown here.

4. FIRST AID MEASURES

Eye Contact	Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Keep eye wide open while rinsing. Consult a physician.
Skin Contact	Wash skin with soap and water. In the case of skin irritation or allergic reactions see a physician.
Inhalation	Move to fresh air. If breathing is difficult, give oxygen. If not breathing, give artificial respiration. Consult a physician.
Ingestion	Do NOT induce vomiting. Call a physician or Poison Control Center immediately. Drink plenty of water. Never give anything by mouth to an unconscious person.
Notes to Physician	May cause sensitization of susceptible persons. Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Flammable Properties	This product does not present fire or explosion hazards as shipped. Small chips, fines, and dust from processing may be readily ignitable.
Flash Point	Not applicable.
Suitable Extinguishing Media	Class D extinguishing agents on fines, dust or molten metal. Use coarse water spray on chips and fines.
Unsuitable Extinguishing Media	DO NOT use halogenated extinguishing agents on small chips or fines. DO NOT use water for fires involving molten metal. These fire extinguishing agents will react with burning material.
Explosion Data	
Sensitivity to Mechanical Impact	None
Sensitivity to Static Discharge	None
Specific Hazards Arising from the Chemical	Thermal decomposition can lead to release of irritating gases and vapors. In the event of fire and/or explosion do not breathe fumes. May cause sensitization by inhalation and skin contact.
Protective Equipment and Precautions for Firefighters	As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

NFPA	Health Hazard 2	Flammability 0	Instability 0	Physical and Chemical Hazards -
HMIS	Health Hazard 2*	Flammability 0	Physical Hazard 0	Personal Protection X

*Indicates a chronic health hazard.

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions	Use personal protective equipment. Keep people away from and upwind of spill/leak.
Environmental Precautions	Prevent further leakage or spillage if safe to do so. Prevent product from entering drains. Do not flush into surface water or sanitary sewer system.
Methods for Containment	Prevent further leakage or spillage if safe to do so.
Methods for Cleaning Up	Avoid dust formation. Collect scrap for recycling. If product is molten, contain the flow using dry sand or salt flux as a dam. All tools and containers which come in contact with molten metal must be preheated or specially coated and rust free. Allow the spill to cool before remelting as scrap.

7. HANDLING AND STORAGE

Handling

Avoid contact with skin, eyes and clothing. Wear personal protective equipment. Avoid dust formation. Keep material dry. Avoid contact with sharp edges or heated material. Hot and cold aluminum are not visually different. Hot aluminum does not always glow red.

Storage

Keep container tightly closed in a dry and well-ventilated place.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Aluminum 7429-90-5	TWA: 1 mg/m ³ respirable fraction	TWA: 15 mg/m ³ total dust TWA: 5 mg/m ³ respirable fraction (vacated) TWA: 15 mg/m ³ total dust (vacated) TWA: 5 mg/m ³ respirable fraction	TWA: 10 mg/m ³ total dust TWA: 5 mg/m ³ respirable dust
Lead 7439-92-1	TWA: 0.05 mg/m ³	TWA: 50 µg/m ³ Action Level: 30 µg/m ³ Poison, See 29 CFR 1910.1025	IDLH: 100 mg/m ³ TWA: 0.050 mg/m ³
Manganese 7439-96-5	TWA: 0.2 mg/m ³	(vacated) TWA: 1 mg/m ³ fume (vacated) STEL: 3 mg/m ³ fume (vacated) Ceiling: 5 mg/m ³ Ceiling: 5 mg/m ³ fume	IDLH: 500 mg/m ³ TWA: 1 mg/m ³ fume STEL: 3 mg/m ³
Molybdenum 7439-98-7	TWA: 10 mg/m ³ inhalable fraction TWA: 3 mg/m ³ respirable fraction	(vacated) TWA: 10 mg/m ³	IDLH: 5000 mg/m ³
Nickel 7440-02-0	TWA: 1.5 mg/m ³	TWA: 1 mg/m ³ (vacated) TWA: 1 mg/m ³	IDLH: 10 mg/m ³ TWA: 0.015 mg/m ³
Silicon 7440-21-3		TWA: 15 mg/m ³ total dust TWA: 5 mg/m ³ respirable fraction (vacated) TWA: 10 mg/m ³ total dust (vacated) TWA: 5 mg/m ³ respirable fraction	TWA: 10 mg/m ³ total dust TWA: 5 mg/m ³ respirable dust
Phosphorus 7723-14-0		TWA: 0.1 mg/m ³ (vacated) TWA: 0.1 mg/m ³	IDLH: 5 mg/m ³ TWA: 0.1 mg/m ³
Vanadium pentoxide 1314-62-1	TWA: 0.05 mg/m ³ V inhalable fraction		IDLH: 35 mg/m ³ V dust and fume Ceiling: 0.05 mg/m ³ V dust and fume 15 min
Tellurium 13494-80-9	TWA: 0.1 mg/m ³	TWA: 0.1 mg/m ³ (vacated) TWA: 0.1 mg/m ³	IDLH: 25 mg/m ³ TWA: 0.1 mg/m ³
Copper 7440-50-8	TWA: 0.2 mg/m ³ fume	TWA: 0.1 mg/m ³ fume TWA: 1 mg/m ³ dust and mist (vacated) TWA: 0.1 mg/m ³ Cu dust, fume, mist	IDLH: 100 mg/m ³ dust, fume and mist TWA: 1 mg/m ³ dust and mist TWA: 0.1 mg/m ³ fume
Sulfur dioxide 7446-09-5	STEL: 0.25 ppm	TWA: 5 ppm TWA: 13 mg/m ³ (vacated) TWA: 2 ppm (vacated) TWA: 5 mg/m ³ (vacated) STEL: 5 ppm (vacated) STEL: 15 mg/m ³	IDLH: 100 ppm TWA: 2 ppm TWA: 5 mg/m ³ STEL: 5 ppm STEL: 13 mg/m ³

ACGIH TLV: American Conference of Governmental Industrial Hygienists - Threshold Limit Value. OSHA PEL: Occupational Safety and Health Administration - Permissible Exposure Limits. NIOSH IDLH: Immediately Dangerous to Life or Health.

Other Exposure Guidelines

Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992). Hexavalent chrome may be formed during welding.

Engineering Measures

Showers
Eyewash stations
Ventilation systems

Personal Protective Equipment

Eye/Face Protection Skin and Body Protection Respiratory Protection

Safety glasses with side-shields.
Impervious clothing. Impervious gloves.
If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.

Hygiene Measures

Do not breathe vapors/dust. When using, do not eat, drink or smoke. Provide regular cleaning of equipment, work area and clothing. Avoid contact with skin, eyes and clothing. Wash hands before breaks and immediately after handling the product. Keep away from food, drink and animal feeding stuffs.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	Metallic, Solid.	Odor	Odorless.
Odor Threshold	No information available	Physical State	Solid
pH	No information available.		
Flash Point	Not applicable.	Autoignition Temperature	No information available.
Decomposition Temperature	No information available.	Boiling Point/Boiling Range	No information available
Melting Point/Range	440-1215°F		
Flammability Limits in Air	No information available.		
Specific Gravity	2.5-2.9	Water Solubility	Insoluble in water.
Solubility	No information available.	Evaporation Rate	No information available
Vapor Pressure	No data available.	Vapor Density	No data available.

10. STABILITY AND REACTIVITY

Stability	Stable under recommended storage conditions.
Incompatible Products	Acids. Alkalies. Metal oxides. Iron powder and water: may cause an explosive reaction forming hydrogen gas when heated above 1470F (800C). Moisture.
Conditions to Avoid	Dust formation. Heat, flames and sparks.
Hazardous Decomposition Products	Iron oxides. Lead oxides. Lead and chromium compounds. Metal fume.
Hazardous Polymerization	Hazardous polymerization does not occur.

11. TOXICOLOGICAL INFORMATION

Acute Toxicity

Product Information

Inhalation

May cause irritation of respiratory tract. Inhalation of fumes may cause metal fume fever, which is characterized by flu-like symptoms with metallic taste, fever, chills, cough, weakness, chest pain, muscle pain and increased white blood cell count.

Eye Contact

Dust contact with the eyes can lead to mechanical irritation.

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
Iron	= 984 mg/kg (Rat)		
Manganese	= 9 g/kg (Rat)		
Nickel	> 9000 mg/kg (Rat)		
Silicon	= 3160 mg/kg (Rat)		
Phosphorus	= 3.03 mg/kg (Rat)	= 100 mg/kg (Rat)	= 4.3 mg/L (Rat) 1 h
Vanadium pentoxide	= 10 mg/kg (Rat)	> 2500 mg/kg (Rat)	= 2.21 mg/L (Rat) 4 h
Tellurium	= 83 mg/kg (Rat)		> 2420 mg/m ³ (Rat) 4 h
Bismuth	= 5 g/kg (Rat)		
Sulfur dioxide		-	Per CGA P-20: 2500 ppm/1hr (Rat)

Chronic Toxicity

Chronic Toxicity

Repeated contact may cause allergic reactions in very susceptible persons. Avoid repeated exposure. Prolonged exposure may cause chronic effects. Repeated or prolonged skin contact may cause skin irritation and/or dermatitis and sensitization of susceptible persons. May cause central nervous system depression with nausea, headache, dizziness, vomiting, and incoordination. May cause adverse effects on the bone marrow and blood-forming system. May cause adverse liver effects.

Elevated temperature processing such as welding and plasma arc cutting may release hazardous fumes. Overexposure to metal fumes may cause pulmonary edema (fluid in the lungs) and methemoglobinemia. May also cause pulmonary fibrosis and lung cancer. Lead compounds may be absorbed by ingestion, by inhalation and through the skin. Lead may damage kidney function, the blood forming system and the reproductive system. Inorganic lead compounds can cause developmental damage.

Carcinogenicity

This product contains one or more substances which are classified by IARC as carcinogenic to humans (Group 1), probably carcinogenic to humans (Group 2A) or possibly carcinogenic to humans (Group 2B).

Chemical Name	ACGIH	IARC	NTP	OSHA
Nickel		Group 2B Group 1	Reasonably Anticipated	X
Chromium		Group 3		
Lead	A3	Group 2A	Reasonably Anticipated	X
Sulfur dioxide		Group 3	-	-
Vanadium pentoxide	A3	Group 2B		X

ACGIH: (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen

IARC: (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans

Group 2A - Probably Carcinogenic to Humans

Group 2B - Possibly Carcinogenic to Humans

NTP: (National Toxicity Program)

Reasonably Anticipated - Reasonably Anticipated to be a Human Carcinogen

OSHA: (Occupational Safety & Health Administration)

X - Present

Target Organ Effects

Blood. Central nervous system (CNS). Eyes. Kidney. Liver. Lungs. Nasal cavities. Respiratory system. Skin.

12. ECOLOGICAL INFORMATION

Ecotoxicity

Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Chemical Name	Toxicity to Algae	Toxicity to Fish	Toxicity to Microorganisms	Daphnia Magna (Water Flea)
Iron	-	LC50 96 h: = 0.56 mg/L semi-static (Cyprinus carpio) LC50 96 h: = 13.6 mg/L static (Morone saxatilis)	-	-
Nickel	EC50 96 h: 0.174 - 0.311 mg/L static (Pseudokirchneriella subcapitata) EC50 72 h: = 0.18 mg/L (Pseudokirchneriella subcapitata)	LC50 96 h: = 1.3 mg/L semi-static (Cyprinus carpio) LC50 96 h: = 10.4 mg/L static (Cyprinus carpio) LC50 96 h: > 100 mg/L (Brachydanio rerio)	-	EC50 48 h: = 1 mg/L Static (Daphnia magna) EC50 48 h: > 100 mg/L (Daphnia magna)
Copper	EC50 96 h: 0.031 - 0.054 mg/L static (Pseudokirchneriella subcapitata) EC50 72 h: 0.0426 - 0.0535 mg/L static (Pseudokirchneriella subcapitata)	LC50 96 h: 0.0068 - 0.0156 mg/L (Pimephales promelas) LC50 96 h: < 0.3 mg/L static (Pimephales promelas) LC50 96 h: = 0.052 mg/L flow-through (Oncorhynchus mykiss) LC50 96 h: = 0.112 mg/L flow-through (Poecilia reticulata) LC50 96 h: = 0.2 mg/L flow-through (Pimephales promelas) LC50 96 h: = 0.3 mg/L semi-static (Cyprinus carpio) LC50 96 h: = 0.8 mg/L static (Cyprinus carpio) LC50 96 h: = 1.25 mg/L static (Lepomis macrochirus)	-	EC50 48 h: = 0.03 mg/L Static (Daphnia magna)
Lead		LC50 96 h: = 0.44 mg/L semi-static (Cyprinus carpio) LC50 96 h: = 1.17 mg/L flow-through (Oncorhynchus mykiss) LC50 96 h: = 1.32 mg/L static (Oncorhynchus mykiss)		EC50 48 h: = 600 µg/L (water flea)
Phosphorus	-	LC50 96 h: 0.001-0.004 mg/L static (Lepomis macrochirus) LC50 96 h: 0.0017-0.0035 mg/L flow-through (Lepomis macrochirus) LC50 96 h: 0.011-0.028 mg/L static (Pimephales promelas) LC50 96 h: 0.015-0.032 mg/L static (Oncorhynchus mykiss) LC50 96 h: > 100 mg/L static (Brachydanio rerio)	-	EC50 48 h: 0.025 - 0.037 mg/L Static (Daphnia magna) EC50 48 h: = 0.03 mg/L (Daphnia magna)

13. DISPOSAL CONSIDERATIONS

Waste Disposal Methods Dispose of in accordance with local regulations.

Contaminated Packaging Do not re-use empty containers.

US EPA Waste Number D007
D008

Chemical Name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
Nickel - 7440-02-0	(hazardous constituent - no waste number)	Included in waste streams: F006, F039		
Chromium - 7440-47-3		Included in waste streams: F032, F034, F035, F037, F038, F039	5.0 mg/L regulatory level	
Lead - 7439-92-1	(hazardous constituent - no waste number)	Included in waste streams: F035, F037, F038, F039, K002, K003, K005, K046, K048, K049, K051, K052, K061, K062, K064, K065, K066, K069, K086, K100, K176	= 5.0 mg/L regulatory level	
Vanadium pentoxide - 1314-62-1	P120			

Chemical Name	RCRA - Halogenated Organic Compounds	RCRA - P Series Wastes	RCRA - F Series Wastes	RCRA - K Series Wastes
Vanadium pentoxide - 1314-62-1		P120		

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste
Nickel	Toxic powder Ignitable powder
Chromium	Toxic Corrosive Ignitable
Manganese	Ignitable powder
Molybdenum	Ignitable powder
Copper	Toxic
Lead	Toxic
Bismuth	Toxic Ignitable
Aluminum	Ignitable powder
Phosphorus	Toxic Ignitable Reactive

14. TRANSPORT INFORMATION

<u>DOT</u>	Not regulated
<u>TDG</u>	Not regulated
<u>MEX</u>	Not regulated

15. REGULATORY INFORMATION

International Inventories

TSCA	Complies
DSL	Complies
EINECS	Complies
ENCS	Complies
IECSC	Complies
KECL	Complies
PICCS	Complies
AICS	Complies

Legend

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

U.S. Federal Regulations

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

Chemical Name	CAS-No	Weight %	SARA 313 - Threshold Values %
Aluminum	7429-90-5	0.01- 0.1	1.0
Lead	7439-92-1	0.15-0.35	0.1
Manganese	7439-96-5	0.25-1.65	1.0
Nickel	7440-02-0	0.01-3.75	0.1
Phosphorus	7723-14-0	0.01-0.04	1.0
Vanadium pentoxide	1314-62-1	0.01-0.25	1.0
Chromium	7440-47-3	0.01-2.50	1.0
Copper	7440-50-8	0.01-0.50	1.0

SARA 311/312 Hazard Categories

Acute Health Hazard	Yes
Chronic Health Hazard	Yes
Fire Hazard	No
Sudden Release of Pressure Hazard	No
Reactive Hazard	No

Clean Water Act

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42):

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Lead		X	X	
Nickel		X	X	
Phosphorus	1 lb			X
Vanadium pentoxide	1000 lb			X
Copper		X	X	

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302):

Chemical Name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
Lead	10 lb		RQ 10 lb final RQ RQ 4.54 kg final RQ
Nickel	100 lb		RQ 100 lb final RQ RQ 45.4 kg final RQ
Phosphorus	1 lb	1 lb	RQ 1 lb final RQ RQ 0.454 kg final RQ
Vanadium pentoxide	1000 lb	1000 lb	RQ 1000 lb final RQ RQ 454 kg final RQ
Chromium			RQ 5000 lb final RQ RQ 2270 kg final RQ
Copper	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ
Sulfur dioxide		500 lb	

U.S. State Regulations**California Proposition 65**

This product contains the following Proposition 65 chemicals:

Chemical Name	CAS-No	California Prop. 65
Lead	7439-92-1	Carcinogen Developmental Female Reproductive Male Reproductive
Nickel	7440-02-0	Carcinogen
Vanadium pentoxide	1314-62-1	Carcinogen

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania	Illinois	Rhode Island
Aluminum	X	X	X		X
Lead	X	X	X	X	X
Manganese	X	X	X	X	X
Molybdenum	X	X	X		X
Nickel	X	X	X	X	X
Silicon	X	X	X		X
Phosphorus	X	X	X	X	X
Vanadium pentoxide	X	X	X		X
Tellurium	X	X	X		X
Chromium		X			X
Copper	X	X	X	X	X
Sulfur dioxide	X	X	X		X

International Regulations

Chemical Name	Carcinogen Status	Exposure Limits
Aluminum		Mexico: TWA= 10 mg/m ³
Lead	A3	Mexico: TWA= 0.15 mg/m ³
Manganese		Mexico: TWA 0.2 mg/m ³ Mexico: TWA 1 mg/m ³ Mexico: STEL 3 mg/m ³
Nickel		Mexico: TWA 1 mg/m ³

Chemical Name	Carcinogen Status	Exposure Limits
Silicon		Mexico: TWA 10 mg/m ³ Mexico: STEL 20 mg/m ³
Phosphorus		Mexico: TWA 0.1 mg/m ³ Mexico: STEL 0.3 mg/m ³
Vanadium pentoxide		Mexico: TWA 0.5 mg/m ³
Tellurium		Mexico: TWA 0.1 mg/m ³
Chromium		Mexico: TWA 0.5 mg/m ³
Copper		Mexico: TWA= 1 mg/m ³ Mexico: TWA= 0.2 mg/m ³ Mexico: STEL= 2 mg/m ³
Sulfur dioxide		Mexico: TWA 2 ppm Mexico: TWA 5 mg/m ³ Mexico: STEL 5 ppm Mexico: STEL 10 mg/m ³

Canada

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR.

WHMIS Hazard Class

Non-controlled

Chemical Name	NPRI
Aluminum	X
Lead	X
Nickel	X
Phosphorus	X
Vanadium pentoxide	X
Chromium	X
Sulfur dioxide	X

Legend

NPRI - National Pollutant Release Inventory

16. OTHER INFORMATION

Prepared By Product Stewardship
23 British American Blvd.
Latham, NY 12110
1-800-572-6501

Issuing Date 23-Nov-2011

Revision Date

Revision Note Initial Release.

General Disclaimer

The information provided on this MSDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

End of Safety Data Sheet